



VALUE LCD CCTV MONITOR
MODEL# 15/17/19RTV



15RTV



17/19RTV

Specification		Model No.	15RTV	17RTV	19RTV
Display	Screen Size		15"	17"	19"
	Viewing Area		304.1 x 228.1mm	337.9 mm X 270.3 mm	376.32 mm x 301mm
	Pixel Type		Active Matrix TFT	Active Matrix TFT	Active Matrix TFT
	Max. Resolution		1024 x 768 @ 75Hz	1280 x 1024 @ 75Hz	1280 x 1024 @ 75Hz
	Pixel Pitch		0.297 mm x 0.297mm	0.264 mm x 0.264mm	0.294 mm x 0.294mm
	Brightness		250cd/m ²	300cd/m ²	300cd/m ²
	Contrast Ratio		450:1	700:1	700:1
	Aspect Ratio		4 : 3	4 : 3	4 : 3
	Viewing Angle(H/V)		130°(R+L)/ 110°(U+B)	150°(R+L)/ 135°(U+B)	150°(R+L)/ 135°(U+B)
	Display Color		16.2 Million	16.2 Million	16.7 Million
	Response Time		< 12ms	< 8ms	< 8ms
	Video System		NTSC / PAL	NTSC / PAL	NTSC / PAL
	Audio	Frequency(H)		30 - 62 KHz (H)	56.7 - 75 KHz (H)
Frequency(V)			56 - 75Hz (V)	55 - 77Hz (V)	50 - 75Hz (V)
Interface	Panel Lamp Life		50,000 hours	70,000 hours	70,000 hours
	Built-in Speakers		Yes (2W x 2)	Yes (2W x 2)	Yes (2W x 2)
Transmitter	Gradual Volume Increase		Yes	Yes	Yes
	Video In / Out (BNC type)		1 / 1	2 / 2	2 / 2
	S-Video In / Out		Not Available	1 / 1	1 / 1
	RGB In (15Pin D-sub)		1	1	1
	Component In		Not Available	Not Available	Not Available
	DVI In		Not Available	Not Available	Not Available
	Audio In / Out (RCA type)		1 / No	1 / No	1 / No
Special Features	PC Stereo Input		1	1	1
	Remote Controller		Yes	Yes	Yes
	PIP (Picture In Picture)		Not Available	Not Available	Not Available
	Filter type		RGB Vertical Stripe Color Filter	3D Comb Filter	3D Comb Filter
	USB Hub		Not Available	Not Available	Not Available
	DC 12V Power Outlet		Not Available	Not Available	Not Available
	LCD Protection Glass		Not Available	Yes	Yes
	Rack Mountable Kit		Optional	Optional	Optional
	Camera Mounting Hole		Not Available	Not Available	Not Available
	Multi-lingual Language		English, Spanish, French, German, Italian	English, Spanish, French, German, Italian	English, Spanish, French, German, Italian
Dimension	VESA™ DDC Compatible		Yes	Yes	Yes
	Outline Dimension (With Stand)		14.96"x 15.15"x 7.48" (380 x 385 x 190mm)	15.0" x 15.35" x 7.87" (382 x 390 x 200 mm)	17" x 16.6" x 7.9" (430 x 421 x 200 mm)
	Outline Dimension (Without Stand)		14.96"x 15.15"x 2.16"(380 x 327 x 55mm)	15.0" x 12.9" x 2.31" (382 x 330 x 58.7mm)	17" x 14.6" x 2.3" (430 x 371 x 58mm)
	Packaging dimension		TBD	17.2" x 18.7" x 8.9" (436.8 x 475 x 226mm)	19.3" x 19.9" x 8.9" (490 x 505 x 225mm)
	Net Weight		TBD	13.1 lbs (5.94 Kg)	14.6 lbs (6.6 Kg)
	Gross Weight		TBD	16.9 lbs (7.66 Kg)	18.6 lbs (8.4 Kg)
Cabinet	Finish / Tilt Stand		Black / Yes	Black / Yes	Black / Yes
	VESA Mounts size		75 x 75mm (BS M4 x 10mm Screw)	100 x 100mm (BS M4 x 10mm Screw)	100 x 100mm (BS M4 x 10mm Screw)
Warranty	Parts / Labor		1 Year / 1 Year	1 Year / 1 Year	1 Year / 1 Year
	MTBF (Approx.)		50,000 hours.	70,000 hours.	70,000 hours.
Regulations			TUV-NRTL (Same as UL), CB, FCC(B), CE-Emc(LVD)	TUV-NRTL (Same as UL), CB, FCC(B), CE-Emc(LVD)	TUV-NRTL (Same as UL), CB, FCC(B), CE-Emc(LVD)
Power Consumption	< On / < Stand-by		<26W / Power Saving (EPA,VESA DPMS,Nutek Compliant)	<36 W / Power Saving (EPA,VESA DPMS,Nutek Compliant)	<42 W / Power Saving (EPA,VESA DPMS,Nutek Compliant)
Power Type	Electrical Ratings		DC 12V / 3A	DC 12V / 4A	DC 12V / 4A
Circumstance	Operating Temperature		10-40°C / 50-104°F	10-40°C / 50-104°F	10-40°C / 50-104°F