



ALTV2416

### **Overview**

ALTV2416 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

#### ***Input:***

- 115VAC, 50/60Hz, 1.9 amp.

#### ***Output:***

- Sixteen (16) fuse protected outputs.
- 24VAC @ 8 amp (192VA) supply current  
(0.5 amp per device, 3.5 amp max.)
- or 28VAC @ 7 amp (196VA) supply current  
(0.438 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 98.27 BTU/Hr.
  - 28VAC: 100.32 BTU/Hr.

#### ***Electrical (cont'd):***

- System AC input VA requirement: 218.5VA.

#### ***Features:***

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.  
(all models w/primary and/or secondary fuses).

#### ***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm).
- Product weight (approx.): 9.1 lbs. (4.1 kg).
- Shipping weight (approx.): 10.1 lbs. (4.6 kg).

### **Agency Approvals**



European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)

