



ALTV2432600CB

**Overview**

ALTV2432600CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via thirty-two (32) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 5.4 amp.

***Output:***

- Thirty-two (32) PTC protected outputs.
- 24VAC @ 28 amp (700VA) supply current  
(0.875 amp per device, 2.5 amp max.)
- or 28VAC @ 25 amp (700VA) supply current  
(0.781 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 343.94 BTU/Hr.
  - 28VAC: 358.28 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement: 621VA.

***Features:***

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
13.5" x 13" x 3.25" (343mm x 330mm x 83mm)
- Product weight (approx.): 24.6 lbs (11.16 kg).
- Shipping weight (approx.): 25.6 lbs (11.61 kg).

**Agency Approvals**

European Conformity

***Enclosure Dimensions (H x W x D approximate):***  
 13.5" x 13" x 3.25" (343mm x 330mm x 83mm)

