

**Overview**

ALTV244300CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 2.7 amp.

***Output:***

- Four (4) PTC protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current (3.13 amp per device, 2.5 amp max.) or 28VAC @ 10 amp (300VA) supply current (2.5 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 153.55 BTU/Hr.
  - 28VAC: 143.31 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement: 310.5VA.

***Features:***

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.): 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)
- Product weight (approx.): 11.1 lbs. (5.1 kg).
- Shipping weight (approx.): 11.7 lbs. (5.3 kg).

**Agency Approvals**

**Enclosure Dimensions (H x W x D approximate):**  
 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)

