



### **Overview**

ALTV248300ULCB provides 24VAC or 28VAC distributed via Eight (8) Class 2 Rated PTC protected power-limited outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

#### ***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

#### ***Output:***

- Eight (8) Class 2 Rated PTC protected power-limited outputs.
- 24VAC @ 12.5 amp (300VA) supply current (1.563 amp per device, 2.5 amp max.) or 28VAC @ 10 amp (280VA) supply current (1.25 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 153.55 BTU/Hr.
  - 28VAC: 143.31 BTU/Hr.

#### ***Electrical (cont'd):***

- System AC input VA requirement: 310.5VA.

#### ***Features:***

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.

#### ***Mechanical:***

- Enclosure Dimensions (H x W x D approx.): 12" x 7.5" x 4.5" (304.8mm x 190.5mm x 114.3mm)
- Product weight (approx.): 11.1 lbs (5.1 kg).
- Shipping weight (approx.): 12.1 lbs (5.5 kg).

### **Agency Approvals**



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
 12" x 7.5" x 4.5" (304.8mm x 190.5mm x 114.3mm)

