



Overview

ALTV248UL provides 24VAC or 28VAC distributed via Eight (8) fuse protected power-limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 0.9 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 3.5 amp (85VA) supply current
(0.438 amp per device, 3.5 amp max.)
or 28VAC @ 3 amp (85VA) supply current
(0.375 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 42.99 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 103.5VA.

Features:

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)
- Product weight (approx.): 6 lbs (2.7 kg).
- Shipping weight (approx.): 7 lbs. (3.2 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D approximate):
 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)

