

# PD4UL

## UL Listed Power Distribution Module

### Description

Altronix PD4UL UL Listed Sub-Assembly power distribution module is designed to convert a single AC or DC input into four (4) individually fuse protected outputs.



PD4UL

### Specifications

#### Input

**Voltage Range** 12VDC or 24VDC, up to 10A or  
24VAC or 28VAC, up to 12A.

#### Outputs

Four (4) fuse protected outputs.  
2.5A per output max.  
Total output current should not exceed max current rating of power supply employed.  
Fuses are rated @ 3.5A/250V.

#### Indicators (LED)

**DC Output** Power LED.

#### Agency Listings

**UL:**  
Access Control UL294  
Burglar Alarm UL603  
Fire Alarm UL1481

#### cUL:

General Signaling Equipment Evaluated to  
CSA Standard C22.2 No.205-M1983.  
Power Supplies for Burglar Alarm Systems  
ULC-5318-96.

#### Physical and Environmental

**Dimensions (W x L x H)**  
3.25" x 5.25" x 1" (82.55mm x 133.35mm x 25.4mm).  
**Product Weight** 0.15 lbs. (0.07 kg).  
**Shipping Weight** 0.25 lbs. (0.11 kg).  
**Temperature**  
Operating 0 to 49° C (32 to 120° F).  
Storage -20 to 70° C (-4 to 158° F).  
Relative Humidity 85% +/-5%.