



R2416UL AC Rack Mount CCTV Power Supply

Rev. DSR2416UL_03262014



R2416UL

Overview

R2416UL provides 24VAC or 28VAC distributed via sixteen (16) fuse protected outputs for powering CCTV cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 2.9 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 24VAC @ 7 amp (175VA) supply current (0.4375 amp per device, 3.5 amp max.) or 28VAC @ 6 amp (175VA) supply current (0.375 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 89.57 BTU/Hr.
- System AC input VA requirement: 333.5VA.

Features:

- Sixteen (16) power LEDs.
- Illuminated master power disconnect circuit breaker with manual reset.
- 3-wire grounded line cord.
- Removable terminal blocks with locking screw flange.
- Spare fuses provided.

Mechanical:

- 2U rack mount chassis for use in standard EIA 19" rack.
- Enclosure Dimensions (H x W x D approx.): 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
- Product weight (approx.): 16.15 lbs. (7.33 kg).
- Shipping weight (approx.): 17.15 lbs. (7.78 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D approximate):
 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)

