

SMP10C24X Series Power Supply/Chargers

Description

Altronix SMP10C24X series power supply/chargers convert a 115VAC, 50/60Hz input into a single, four (4), eight (8) or sixteen (16) fuse/PTC protected outputs. Outputs are 24VDC with a total of 10A max.



SMP10PM24P4CB

Key Features

- Available with 1, 4, 8 or 16 outputs
- Fused or PTC protected outputs
- Supervision (where applicable, see Chart below):
 - AC Fail
 - Battery Fail and Low Battery
- Built-in charger for sealed lead acid or gel type batteries
- Instantaneous transfer to stand-by batteries
- Short circuit and overload protection
- Power On/Off switch
- Lifetime Warranty / Made in the U.S.A.

SMP10C24X Series Power Supply Configuration Reference Chart

Altronix Model Number	Accessory Power Distribution Module(s)	Number of Outputs	Fused Outputs	PTC Outputs	Individual Output Rating (A)	Supervised	115VAC, 50/60Hz Input Current (A)	24VDC Total Output Current (A)	Accommodates Batteries
SMP10C24X	-	1	-	-	10A	-	2.7A	10A	Two (2) 7AH
SMP10PMC24X			-	-	10A				
SMP10PM24P4	PD4	4	✓	-	3.5A	✓			
SMP10PM24P4CB	PD4CB		-	✓	2.5A				
SMP10PM24P8	PD8	8	✓	-	3.5A				
SMP10PM24P8CB	PD8CB		-	✓	2.5A				
SMP10PM24P16	PD16W	16	✓	-	3.5A				
SMP10PM24P16CB	PD16WCB		-	✓	2.5A				

SMP1024CX Series

Power Supply/Chargers



Specifications

Input

Voltage 115VAC, 50/60Hz

Outputs

Voltage 24VDC
 Current 10A @ 24VDC continuous max
 Protection Fused 3.5A / PTC 2.5A
 Other Overvoltage protection
 Filtered and regulated

Back-up Battery *(not included)*

Capacity 7AH / 12VDC (2 within enclosure)
 40 AH / 65 AH (requires separate enclosure)
 Type Sealed lead acid or gel type
 Charging current 0.7A
 Failover Upon AC loss, instantaneous

Supervision *(where applicable)*

AC Failure Form "C" contacts
 Battery Low/Fail Form "C" contacts

Indicators (LED)

Input 115VAC is present
 DC Output Powered

Physical and Environmental

Dimensions (H x W x D)
 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

Product Weight / Shipping (approx.)

Model	Product Weight	Shipping Weight
SMP10(PM)C24X	8.3 lbs. (3.76 kg)	9.3 lbs. (4.22 kg)
SMP10PM24P4(CB)	8.5 lbs. (3.85 kg)	9.5 lbs. (4.31 kg)
SMP10PM24P8(CB)	8.6 lbs. (3.90 kg)	9.6 lbs. (4.35 kg)
SMP10PM24P16(CB)	8.8 lbs. (3.99 kg)	9.8 lbs. (4.44 kg)

Temperature

Operating 0 to 49° C (32 to 120° F)
 Storage -20 to 70° C (-4 to 158° F)
 Relative Humidity 85% +/-5%

BTU/Hr:
 122.84 BTU/Hr.