

1/3" INDOOR DAY/NIGHT MINI-ARMORDOME CAMERA WITH INFRA-RED LED ILLUMINATORS



- True Day/Night Operation
- 14 Infra-Red LED Illuminators
- Mini High Impact Armordome
- Tamper-Proof Housing

	DC-12 Volt		AC-24 Volt	
MODEL	WDD-7500DN	WDD-7505DN	WDD-6400DN	WDD-6405DN
Video				
Imager	1/3" Color CCD		1/3" Color CCD	
Pixels	512 (H) x 492 (V) NTSC	768 (H) x 494 (V) NTSC	512 (H) x 492 (V) NTSC	768 (H) x 494 (V) NTSC
Resolution	400 TVL	480 TVL	400 TVL	480 TVL
Minimum Illumination	0 LUX (IR LEDs ON)		0 LUX (IR LEDs ON)	
S/N Ratio	48dB		48dB	
Shutter Speed	1/60~1/100,000 Sec.		1/60~1/100,000 Sec.	
Gamma	0.45		0.45	
White Balance	Auto White Balance		Auto White Balance	
Automatic Gain Control	Yes		Yes	
Video Output	1.0 Vp-p Composite, 75Ohm		1.0 Vp-p Composite, 75Ohm	
Connectors				
Power Input	Barrel Plug Connector		Bare Wire Leads	
Video Output	BNC Connector		BNC Connector	
Electrical				
Power Input	DC-12Volt		AC-24 Volt	
Current Consumption	7.2 Watts		7.2 Watts	
Physical				
Lens Type	Fixed 3.6mm (Others Available)		Fixed 3.6mm (Others Available)	
LEDs	14 Individual Super Infra-Red LEDs		14 Individual Super Infra-Red LEDs	
LED Range	30ft		30ft	
Dimensions	3.85" (Dia) x 2.7" (H)		3.85" (Dia) x 2.7" (H)	
Operational Temperature	+4 Deg. F to 158 Deg. F		+4 Deg. F to 158 Deg. F	
Accessories (Optional)	Power Supply - Weldex WDADP-12/1A		Power Supply - Weldex WDADP-24	

* Specifications subject to change without prior notice.

WELDEX CAN CUSTOMIZE CAMERAS FOR YOUR SPECIFIC NEED!!