



SPECIFICATION

- Simplex function
- Programming the MENU OSD (on screen display)
- Real time quad display
- Full, quad, PIP & POP display mode
- Built-in time, date, title generator
- RS-232C full function remote control (option)
- Alarm input with built-in buzzer and alarm out
- Alarm status record
- Alarm time zone selectable
- Buzzer for alarm in / out
- Freeze function
- 4channels full motion detection function
- Time laps VCR support
- Programmable dwell time (1 ~ 99 sec)
- Power on list record display
- Video loss list record display
- Alarm event list record display
- Digital 2x zoom in VCR playback mode
- Buzzer on / off function
- Border line on / off function
- Auto sequential roll free function
- Small size: 200(w) x 43(h) x 170(d)mm

Video input	1Vp-p, 75Ohm, BNC, 4ch
Vcr input	1Vp-p, 75Ohm, BNC
Monitor output	1Vp-p, 75Ohm, BNC
VCR output	1Vp-p, 75Ohm, BNC
Alarm	4ch individual on / off, OSD display & buzzer, time zone selectable, Alarm event record display till 30 lists (YY/MM/HH/SS, CH), alarm out (open collector)
Video loss	OSD display & buzzer, alarm event record display till 30 lists (YY/MM/HH/SS, on / off CH), video loss out (open collector)
OSD display	Camera ID display: 8 characters, camera ID display on / off selectable time / date display (YY/MM/DD, HH/MM/SS), time date display selectable
Power on event	power on event record display
Zoom	2x zoom mode VCR playback
Power supply	2A DC5V
Dimension	7.9"(W) x 1.7"(H) x 6.7"(D)
Weight	2.2lbs